

PAXXAL PALLET

PAXXAL PALLET
CATALOG NUMBER

S62



version: 033016

SPECIFICATIONS

MATERIAL:	Virgin High Density Polyethylene with Solid-Filled Core	
FORK ENTRY:	4-Way Entry	
DIMENSIONS:	48 in x 40 in x 6.3 in	16 cm x 120 cm x 100 cm
WEIGHT:	62 lbs	28 kg
UNSUPPORTED EDGE-RACKABLE:	2,205 lbs	1,000 kg
DYNAMIC LOAD:	5,512 lbs	2,500 kg
STATIC LOAD:	22,046 lbs	10,000 kg



Paxxal Pallets comply with the guidelines of USDA & FDA and have been ISO 96:11 tested by Virginia Tech's Center for Packaging and Unit Load Design.

DESCRIPTION

All Paxxal Pallets are made with a virgin HDPE outer shell and a proprietary, solid-filled inner core. This patented mixture combined with our unique rotomolding process creates a pallet with a solid-filled core that is stronger and more impact resistant than standard plastic pallets. Fill ports are hermetically sealed and the top and bottom pieces are joined together by a unique, integrated, central locking mechanism and fusion welded on each leg.

MAIN ATTRIBUTES


- ✓ Unsurpassed durability
- ✓ Slip-resistant top deck
- ✓ Perimeter lip to increase load stability
- ✓ Contoured legs to guide forklift
- ✓ Pass-through top deck for fast drying
- ✓ Constant dimensions for automated systems
- ✓ Less combustible than plastic alone
- ✓ Excellent resistance to extreme temperatures, bacterial growth, corrosion, creep, and UV
- ✓ Zero distortion -40°F to 170°F
- ✓ Exempt from fumigation requirements
- ✓ 100% recyclable

APPLICATION

Paxxal is committed to your success. To ensure this pallet meets your operational needs, we provide free-of-charge, returnable Paxxal assessment pallets. All Paxxal pallets are manufactured via fully-automated, custom-developed rotational mold pallet manufacturing equipment to ensure product consistency.

PAXXAL PALLET

SOLID-FILLED / SOLID PERFORMANCE



STRONG

Vibration-absorbing aerated core and even wall thickness prevents product damage



SMART

All pallets are uniquely encoded with RFID and Data Matrix Barcode



SANITARY

Sealed surface and drainage vents discourage moisture and contamination risks



SUSTAINABLE

100% Recyclable reduces environmental impact.

OUTPERFORMS OTHER PALLET

- More durable than wood or plastic
- Higher impact resistance
- Non-brittle in extreme temperature
- Exceptional performance in all climates
- Zero distortion -40°F to 170°F
- Can be color coded and branded

DESIGNED FOR OPTIMAL PERFORMANCE

- Ideal for automated environments
- Won't crack or break under low temperatures
- Resistant to bacteria, corrosion, creep and UV
- Extremely simple to sterilize and clean

DESIGNED TO REDUCE OVERALL COSTS

- Exempt from fumigation requirements
- 100% recyclable
- RFID tracking options readily available



Uniquely
Rotomolded

Award Winning



Best pallet for all of your closed-loop
or in-house applications

Order A Sample Today!

+1-317-296-7724

SILUMA@PAXXAL.COM